


# PPC-1727



17" Rugged Panel PC, Core Duo 2.13G, Touch, VGA, HDMI, Dual LAN, 6 COM, 6 USB, PS2 KB/Mouse, Speakers, PCI, Touchscreen, SB=Stainless Steel , AL = Aluminium , Windows XP Pro or 7 - 32/64bit

## TECHNICAL SPECIFICATIONS

### LCD Display Grade

LCD Size	17" Active Matrix TFT LCD
Resolution	1280 x 1024 resolution (Option:1920 x 1080)
Aspect Ratio	4:3 standard ratio
Luminance	380cd/m2 (or higher)
Color Depth	16.7M true colors
Contrast Ratio	1000 : 1 (typical)
Backlight	LED backlight
Viewing Angle	80(U) x 80(D) x 85(L&R)
Touch Screen	17" 5-Wire Resistive Touch
Touch Resolution	4096 x 4096

### Mechanical

Front Bezel	Aluminium (AL) or Stainless Steel (SB)
Construction	Heavy-duty rugged steel construction
Mounting	Panel Mount and Quick Mount
Wall Mounting	Rear and VESA wall mount
IP Rating	IP-65 Front / IP-54 Rear and Sides
Expansion Slots	Optional PCI / PCI-e, CF and 2 x Sata
Cut-out	(ICP) 383.6 x 282.6mm / (STD) 397.4 x 328.0mm

### System

Chipset	Intel® NM10 Cedar Trail
CPU	Intel® fanless D2700 Core Duo 2.13GHz CPU
System Memory	4GB upto 32GB DDR3 memory
HDD or SSD	120, 250, 320G anti-shock HDD (Option : SSD)
DirectX / open GL	Support DirectX 10.1 and open GL 3.2
VGA / RGB Port	VGA port support 2 <sup>nd</sup> independent display
HDMI Port	Support HDMI Definition video & audio signals
Graphics Chip	Intel® GMA 3600 graphics card
DVMT Technology	Support Dynamic Video Management Tech
LAN	Dual Giga bit LAN support 10/100/1000 Mbps
COM (Serial)	5 x COM Ports (Option: 6 COM)
USB Port	6 x USB2.0
PS2 Ports	PS2 Keyboard and PS2 Mouse
Audio In-Out Port	Audio-in and Audio-out Ports
Speakers	Built-in 2 speakers
Digital I/O (Option)	Optional 4 Digital Input and 4 Digital Output

### Power and Environmental

AC Power Source	External AC adapter support 90 up to 264V
DC Power Source	Support DC 12V Power source
Option : DC9~32V	Optional DC9~32V is available at extra cost
Safety Approval	Power adapter is UL, cUL, TUV Approval
Operate Temp	-5 to 60 degrees Celcius
Storage Temp	-20 to 75 degrees Celcius
Shock	Meet MIL-STD-810F shock standard
Vibration	Meet MIL-STD-810F vibration standard
Compliance	Meet CE, FCC, RoHS standard



Suite 603, Level 5  
152 Bunnerong Road  
PAGEWOOD  
NSW, 2035  
Tel: 02 9314 2092 Email: sales@icpglobal.com.au